

Argotec™ Graphic Film 46010 White

General Description

Typical application: Performance printable facestock

Polymer: Aliphatic polyurethane (TPU)

Key attribute: Class A gloss finish, Highly conformable, Excellent abrasion resistance, Excellent low-temperature flexibility & cold-crack resistance, UV resistant, No additives, Consistent, Excellent adhesive compatibility/anchorage, Halogen free

Property	Method	Typical Value
Gauge	N/A	1.0 - 4.0 mils
Width	N/A	Up to 62" (1.57 m)
Roll Length	N/A	Up to 1500 non-spliced yards ²
Tensile strength @ 100%	ASTM D-412	6000 psi (41 MPa)
Elongation at break	ASTM D-412	300%
UV resistance (yellowing)	ASTM D-4329 cycle B ¹	Change in Yellowness Index (ΔYi) < 1.5 at 2000 hrs
Gloss, 60°	OTM 3-309	93%
Haze	ASTM D-1003	1%
Resin Hardness	ASTM D-2240	Shore 60D

¹QUV using UVA 340 bulb, 8 hours 70°C, 4 hours 50°C condensation

²Dependant on gauge

REACH Compliance: This product does not contain substances on the REACH/SVHC Candidate List at >0.1%

Note: Suitable for backside paper, poly coated paper, or matte textured film release liner to prevent blocking.