

# Argotec™ AU25

## General Description

Breathable transparent medical grade aliphatic polyether polyurethane/urethane/TPU film-on-paper carrier. The product is intended for use in any application where it is important that the film does not discolour when gamma sterilized.



Typical Property	Value
Thickness	23 microns
Film weight	25 g/m <sup>2</sup>
MVTR, upright (g/m <sup>2</sup> per 24 shrs @37° C/98.6° F)	1000
Tensile strength MD	800 gf/cm
Tensile strength TD	800 gf/cm
Nominal length @ max width	1000 lm
Minimum length	50 lm
Minimum width	1280 mm
Carrier	100 gsm release coated paper
Stripping load (release)	1.5 gf/m
Elongation at break, MD	400%
Elongation at break, TD	400%

[info@argotec.com](mailto:info@argotec.com)  
[argotec.com](http://argotec.com)

Copyright ©Mativ Holdings, Inc. (2023). All Rights Reserved. ARGOTEC™ is trademarks of Mativ Holdings, Inc. ("Mativ") or an affiliated company of Mativ.

All statements, product characteristics, and performance data contained herein are believed to be reliable based on observation and testing, but no representations, guarantees, or warranties of any kind are made as to accuracy, suitability for particular applications, or the results to be obtained. Nothing contained herein is to be considered to be permission or a recommendation to use any proprietary process or technology without permission of the owner. No warranty of any kind, expressed or implied, is made or intended.