

Argotec[™] EU31 Beige

General Description

Beige coloured breathable medical grade polyurethane/urethane/TPU fi Im on paper carrier.

Typical Property	Value
Thickness	30 microns
Weight	32 g/m²
MVTR, upright (per 24 hrs @ 37°C)	3000 g/m²
MVTR, inverted (per 24 hrs @ 37°C)	14000 g/m²
Tensile strength MD	1100 gf/cm
Tensile strength TD	1000 gf/cm
Nominal length at max width	1000 lm
Minimum width	50 mm
Maximum width	1300 mm
Carrier	100 gsm single sided release paper
Liner	n/a
Adhesive	n/a
Stripping load (release)	2.0 gf/cm
Elongation at break, MD	700%
Elongation at break, TD	700%
Other information	Low coefficient of friction, switchable. NB under validation.

info@argotec.com argotec.com

ARG_TDS_V01_20240513

Copyright @Mativ Holdings, Inc. (2024). All Rights Reserved. ARGOTEC m is trademarks of Mativ Holdings, Inc. ("Mativ") or an affiliated company of Mativ.

All statements, product characteristics, and performance data contained herein are believed to be reliable based on observation and testing, but no representations, guarantees, or warranties of any kind are made as to accuracy, suitability for particular applications, or the results to be obtained. Nothing contained herein is to be considered to be permission or a recommendation to use any proprietary process or technology without permission of the owner. No warranty of any kind, expressed or implied, is made or intended.