

Argotec[™] EU40

General Description

EU40 is a breathable, transparent, polyurethane/urethane/TPU film on a paper carrier.

Typical Property	Value
Thickness	36 microns
Weight	38 g/m²
MVTR, upright (per 24 hrs @ 37°C)	2900 g/m²
Tensile strength MD	750 gf/cm
Tensile strength TD	750 gf/cm
Nominal length at max width	1000 lm
Minimum width	50 mm
Maximum width	1300 mm
Carrier	73 gsm single-sided release paper
Liner	n/a
Adhesive	n/a
Stripping load (release)	1.0 gf/cm
Elongation at break, MD	700%
Elongation at break, TD	700%

info@argotec.com argotec.com

ARG_TDS_V01_20240513

Copyright \odot Mativ Holdings, Inc. (2024). All Rights Reserved. ARGOTEC^{M} is a trademark of Mativ Holdings, Inc. ("Mativ") or an affiliated company of Mativ.

All statements, product characteristics, and performance data contained herein are believed to be reliable based on observation and testing, but no representations, guarantees, or warranties of any kind are made as to accuracy, suitability for particular applications, or the results to be obtained. Nothing contained herein is to be considered to be permission or a recommendation to use any proprietary process or technology without permission of the owner. No warranty of any kind, expressed or implied, is made or intended.