

## **Argotec™ EU50/A16**

## **General Description**

EU50/A16 is a colorless polyurethane film (EU50) coated with a high tack acrylic adhesive (A16). It is supplied with a single-sided, release coated paper liner.

## **Key Features**

- Waterproof
- Breathable
- Bacterial barrier
- Conformable
- High tack skin contact adhesive

## **Key Features**

- Manufactured in bulk rolls up to 1300mm by 1000m (coated width 1280 nominal)
- Rolls can be slit to customer's requirements

Property	Test Method	Typical Value
Film weight	GK01	55 gm <sup>-2</sup>
Film thickness	GK10	50 microns
Adhesive weight	GK57	26 gm <sup>-2</sup>
Liner stripping load/release	GK56	5 gf/cm <sup>-1</sup>
Adhesion to stainless steel	GK55	480 gf/cm <sup>-1</sup>
Moisture vapour transmission rate, MVTR (24 hours @ 37°)	GK54	440 lm

info@argotec.com argotec.com

ARG\_TDS\_V01\_20240513

Copyright  $\odot$ Mativ Holdings, Inc. (2024). All Rights Reserved. ARGOTEC<sup> $\mathrm{M}$ </sup> is a trademark of Mativ Holdings, Inc. ("Mativ") or an affiliated company of Mativ.

All statements, product characteristics, and performance data contained herein are believed to be reliable based on observation and testing, but no representations, guarantees, or warranties of any kind are made as to accuracy, suitability for particular applications, or the results to be obtained. Nothing contained herein is to be considered to be permission or a recommendation to use any proprietary process or technology without permission of the owner. No warranty of any kind, expressed or implied, is made or intended.

