

Coretec™ FEP Specifications (Fluorinated Ethylene Propylene)

General Description

- Water absorption: 24 hour < 0.01% (ASTM D570)
- Weather and chemical resistance: Outstanding
- FEP is ASTM D2116 Type IV

Physical Property	Test Method	Value
Specific gravity	ASTM D792	2.12 - 2.17
Color		Natural
Mechanical Property	Test Method	Value
Tensile strength	ASTM D638	4350 psi (30MPa)
Elongation	ASTM D638	325%
Hardness		D56
Thermal Property	Test Method	Value
Melting point		255°C (491°F)
Electrical Property	Test Method	Value
Dielectric strength	ASTM D149	>100 (kV/mm)
Dissipation factor	ASTM D150	1kHZ 0.0005

info@argotec.com argotec.com

COR_TDS_V01_20240514

Copyright ©Mativ Holdings, Inc. (2024). All Rights Reserved. ARGOTEC™ and Coretec™ are trademarks of Mativ Holdings, Inc. ("Mativ") or an affiliated company of Mativ.

All statements, product characteristics, and performance data contained herein are believed to be reliable based on observation and testing, but no representations, guarantees, or warranties of any kind are made as to accuracy, suitability for particular applications, or the results to be obtained. Nothing contained herein is to be considered to be permission or a recommendation to use any proprietary process or technology without permission of the owner. No warranty of any kind, expressed or implied, is made or intended.

